

Part Number	Max Length	Min Length	Stroke	Test Velocity (in./sec.)	Compression Force (lbs.)	Rebound Adjustment Position // Forces (lbs.)			
						0	1	2	3
30 5325	15.75"	10.75"	5"	2.05"	20	65	70	95	125
30 6325	18.25"	12.25"	6"	5.16"	40	160	180	225	275
30 7325	19.75"	12.75"	7"	10.32"	60	280	325	390	490
30 8325	22.25"	14.25"	8"	13.00"	70	345	405	495	630
30 9325	23.75"	14.75"	9"	15.49"	80	380	450	550	750
				20.65"	100	510	595	720	935
				26.00"	125	675	790	965	1280
30 5436	15.75"	10.75"	5"	2.05"	45	100	110	120	145
30 6436	18.25"	12.25"	6"	5.16"	65	175	195	225	275
30 7436	19.75"	12.75"	7"	10.32"	90	285	330	385	490
30 8436	22.25"	14.25"	8"	13.00"	110	340	400	470	590
30 9436	23.75"	14.75"	9"	15.49"	120	395	450	560	710
				20.65"	150	520	605	735	905
				26.00"	180	650	765	900	1180
30 7514	19.75"	12.75"	7"	2.05"	75	50	60	70	85
				5.16"	125	85	90	105	125
				10.32"	180	135	155	180	230
				13.00"	225	155	185	225	280
				15.49"	240	180	215	265	335
				20.65"	305	240	275	335	450
				26.00"	380	310	360	450	565
30 7647	19.75"	12.75"	7"	2.05"	110	115	135	150	185
				5.16"	165	235	255	295	360
				10.32"	220	320	365	435	550
				13.00"	240	370	420	505	650
				15.49"	265	410	485	580	735
				20.65"	310	500	595	710	925
				26.00"	350	575	685	805	1095
30 8414	22.25"	14.25"	8"	2.05"	25	15	20	25	35
30 9414	23.75"	14.75"	9"	5.16"	60	50	65	75	100
				10.32"	120	100	115	150	200
				13.00"	155	135	155	200	260
				15.49"	175	150	175	225	300
				20.65"	220	220	265	325	420
				26.00"	265	275	330	420	530
30 9525	23.75"	14.75"	9"	2.05"	100	70	85	95	105
				5.16"	135	110	135	155	175
				10.32"	155	175	215	255	310
				13.00"	200	210	255	300	385
				15.49"	220	235	300	355	465
				20.65"	260	300	385	475	615
				26.00"	290	365	465	560	715